

MOORING REGULATIONS

ALL OWNERS ARE RESPONSIBLE FOR ACQUIRING AND MAINTAINING THEIR OWN TACKLE. THE VILLAGE OF SAG HARBOR MAKES NO WARRANTY EXPRESSED OR IMPLIED, AS TO THE ADEQUACY OF THE STANDARDS LISTED BELOW FOR ANY SPECIFIC VESSEL.

REGISTERED BOAT LENGTH FEET	MUSHROOM ANCHOR POUNDS	BOTTOM CHAIN LINE	TOP CHAIN LINE	PENNANTS NYLON/ DACRON
Under 16	100	3/8"	5/16"	1/2"
16-19	200	3/8"	5/16"	1/2"
20-25	250	1/2"	3/8"	5/8"
26-30	350	5/8"	1/2"	3/4"
31-35	500	5/8"	1/2"	3/4"
36-40	700	5/8"	1/2"	7/8"
41-50	1000	3/4"	5/8"	1"
51+	As required by dock master			

WE WILL ALSO ACCEPT **DOR MOR** STYLE MOORINGS OF THE SAME WEIGHT, **HELIX**, AND **MANTA RAY** MOORINGS.

ALL GROUND TACKLE WILL BE INSPECTED ONCE EVERY TWO YEARS BY A PRIVATE CONTRACTOR AND PROOF OF INSPECTION WILL BE SUBMITTED TO THE HARBOR MASTER'S OFFICE. OFFICAL FORMS MAY BE OBTAINED FROM YOUR CONTRACTOR OR THE HARBOR MASTER'S OFFICE.

SPECIFICATIONS OF TACKLE:

- 1.) ALL MOORING BALLS WILL BE WHITE WITH A BLUE STRIPE. NOTE: THIS IS COAST GUARD REGULATION
- 2.) ALL MOORING BALLS WILL HAVE THEIR GRID LOCATION AND MUSHROOM SIZE ON THEM
- 3.) MOORING TACKLE SHALL MEET THE FOLLOWING MINIMUM REQUIREMENTS
- 4.) ONE ANCHOR PER LOCATION
- 5.) THERE WILL BE TWO PENNANT LINES ON EACH MOORING AND THERE WILL BE CHAFING GEAR ON ALL LINES
- 6.) ALL SHACKLES, SWIVELS, AND RINGS WILL BE SIZED ACCORDING TO THE CHAIN SIZE.
- 7.) ALL RINGS WILL BE FORGED ONLY. NO WELDED RINGS.
- 8.) CHAIN WILL BE NO LONGER THAN TWO AND ONE HALF THE DEPTH OF THE WATER. THE BOTTOM CHAIN WILL BE ONE AND ONE HALF THE DEPTH OF THE WATER AND THE TOP CHAIN WILL BE ONE TIMES THE DEPTH OF THE WATER.
- 9.) PENNANT LINES LENGTH: THE MAXIMUM LENGTH OF THE PENNANT SHALL BE TWO AND ONE HALF TIMES THE DISTANCE FROM THE WATER TO POINT OF ENTRY ON VESSEL.
- 10.) OWNERS ARE EXPECTED TO MAKE PERIODIC INSPECTIONS OF PENNANT LINES, FLOATS, CHAFING GEAR.

MOORINGS ARE NOT TRANSFERABLE. ARRANGEMENTS MAY BE MADE WITH THE LAUNCH OPERATOR FOR APPROVED SUBLETTING.